



LED Slim Exterior Plain

Parameters

Optical Parameters

CCT	3000K/4000K/6000K
Lumen Output(lm)±5%	1200lm
Lumen Efficacy(LPS)±5%	100lm/W
LED Type/Qt'y	SMD 60pcs
CRI/SDCM	>80/<6

Electrical Parameters

Rated Power(w)±5%	12W
Rated/Actual Input	220-240Vac
Driver Output Data	75Vdc/165mA
Power Factor/THD/PE	>0.9
Driver/Connection	Integrated
Over Load/Short Circuit	Protection
Hi-pot Test Range	SELV Isolated driver, 3000Vdc/5mA/60S


Life

Warranty	5 years
Lumen Maintenance 70%	40000hrs
LM80	97.34% lumen maintance@6000hrs


Others

IP/IK/Glow-wire	IP65/IK08/850°C
Temp./Humidity	Working:-20°C~45°C Storage:<70°C

Product Dimension



IK08   IP65



Height	AVR E	CENTER E	Diameter
1.50m	35.47lx	123.97lx	459.34cm
2.00m	19.95lx	69.73lx	612.46cm
4.00m	4.99lx	17.49lx	1224.92cm
4.50m	3.94lx	13.77lx	1378.03cm
6.00m	2.22lx	7.75lx	1837.38cm

Angle: 113.7deg

Quality LED Lighting