



## LED CEILING LAMP EL24WCCT

### Parameters

#### Optical Parameters

|                        |                   |
|------------------------|-------------------|
| CCT                    | 3000K-4000K-6500K |
| Lumen Output(lm)±5%    | 2400lm            |
| Lumen Efficacy(LPS)±5% | 100lm/W           |
| LED Type/Qt'y          | SMD 576pcs        |
| CRI/SDCM               | > 80/ < 6         |

#### Electrical Parameters

|                         |                                      |
|-------------------------|--------------------------------------|
| Rated Power(w)±5%       | 24W                                  |
| Rated/Actual Input      | 220-240V                             |
| Driver Ooutput Data     | 72V 320mA                            |
| Power Factor/THD/PE     | > 0.9                                |
| Driver/Connection       | Integrated                           |
| Over Load/Short Circuit | Protection                           |
| Hi-pot Test Range       | Non-Isolated driver, 3000Vdc/5mA/60S |

#### Life

|                   |                             |
|-------------------|-----------------------------|
| Warranty          | 3 years                     |
| Lumen Maintenance | 30000hrs                    |
| LM80              | 96% lumen maintance@6000hrs |

#### Others

|                 |                                  |
|-----------------|----------------------------------|
| IP/IK/Glow-wire | IP65/IK07/650°C                  |
| Temp./Humidity  | Working:-20°C~45°C Storage:<70°C |

### Product Dimension

